



## WALRUS G4 EXTENSION PACK

EXT-WLRS-96230N-G1

### FAQ

#### How do I connect this battery into my existing system?

Our product uses a standard 175A Anderson connector. A single battery order will include a 175A connector to 175A connector cable for ease of installation.

#### How many times can I put this battery in parallel / series?

This battery is not series capable but can be connected in parallel up to eight times. Make sure that the total amount of these batteries in your configuration never exceeds eight total batteries. When connecting batteries in parallel, make sure all batteries are within 1 volt of one another.

#### What is the warranty on this battery?

We offer a comprehensive 10 year warranty on all of our batteries. You can read more about our warranty at [batteryevo.com/10-years-warranty/](https://batteryevo.com/10-years-warranty/)

#### BATTERY SPECS

Chemistry	NMC
Voltage	96V
Capacity	23kWh
Amp Hours	260Ah
Operating Voltage Range	72V - 99.6V
Charging Voltage	99.6V
Max Charging Voltage	99.6V
Cell Configuration	24S2P

#### BMS SPECS

Max Peak Discharge	26400W (Over 5 Sec)
Max Continuous Power	13320W
Max Continuous Discharge	150A
Max Charge Current	150A
Charge Temp. Range	-20°C (-4°F) / 55°C (131°F)
Discharge Temp. Range	-20°C (-4°F) / 55°C (131°F)
Optimal Discharge Temp. Range	15°C (59°F) / 35°C (95°F)
Storage Temp. Range	-5°C (23°F) / 60°C (140°F) (Max 6 months)

#### BATTERY SIZE

Weight	306lbs. (138.8kg)
Width	24.41in (620mm)
Depth	15.4in (391mm)
Height	22.13in (562mm)



**WARNING:** Avoid serious collisions;  
Do NOT exceed max charging voltage;  
Do NOT drop into water.

## Customer Support